GREASE LUBRICATION SCHEDULE FOR HORIZONTAL SHAFT APPLICATIONS

LINK-BELT® B22400, B22500 & B22600 SERIES ROLLER BEARING UNITS

SHAFT DIA.	GREASE AMOUNT	6 MONTHS RELUBE	4 MONTHS RELUBE	2 MONTHS RELUBE	1 MONTH RELUBE	2 WEEKS RELUBE
3/4 - 1	0.20 oz.	1400	2200	3400	5000	6800
1-1/16 - 1-1/4	0.25 oz.	1150	1800	2800	4500	5600
1-5/16 - 1-1/2	0.30 oz.	1000	1550	2400	3800	4800
1-9/16 - 1-3/4	0.40 oz.	870	1350	2100	3300	4200
1-13/16 - 2	0.45 oz.	700	1100	1700	2700	3400
2-1/16 - 2-1/4	0.55 oz.	630	1000	1500	2400	3000
2-5/16 - 2-1/2	0.65 oz.	580	910	1400	2250	2800
2-9/16 - 3	1.20 oz.	460	730	1100	1800	2200
3-1/16 - 3-1/2	2.00 oz.	410	640	1000	1550	2000
3-9/16 - 4	2.90 oz.	350	550	850	1350	1700
4-1/16 - 4-1/2	3.25 oz.	300	470	740	1150	1500
4-9/16 - 5	5.00 oz.	280	440	680	1050	1400
		Shaft Speed in rpm				

* OPERATING TEMPERATURES LIMITED TO -40 TO +225° F.
* "DIRTY", CORROSIVE OR WET ENVIRONMENTS REQUIRE MORE FREQUENT RE-LUBE.
* MAXIMUM SPEEDS FOR TYPE "H" SEALS.
*** REDUCE LUBRICATION INTERVALS BY HALF FOR VERTICAL SHAFT APPLICATIONS**
* SUGGESTED GREASES ARE: MOBILITH AW2, TEXACO PREMIUM RB, SHELL ALVANIA GREASE 2, GULF CROWN NO.2, AMOCO RYKON 2